



# LusterStone® Basic Application

Apply 2 coats of SetCoat®. For best results choose a color that is similar to the LusterStone® hue. Allow this base to dry for a minimum of 24 hours.

- step 1. Using a ¼” sponge/nap roller, apply an even smooth coat of LusterStone®, moving the roller in a random pattern. If necessary, LusterStone® may be thinned up to 20% with water for this step. Allow LusterStone® to dry overnight.
- step 2. For the second pass, dab a workable amount of LusterStone® onto a stainless steel trowel in a random pattern. Do not overload the trowel.
- step 3. Dot the LusterStone® onto the surface in organic patterns.
- step 4. Using smooth sweeping strokes 6” to 12” in length, smooth out this coat of LusterStone® onto the work surface, keeping the coat even and smooth. Let dry.
- step 5. For the third pass, again apply LusterStone® to the trowel in random areas. Trowel the product onto the surface backfilling the lows and skimming the highs. This technique will remove excess product as the blade skims the surface and burnishes the material.

Once dry, this pass can be repeated again if desired for more shine and a smoother finish as it is a very quick step.

For more shine, LusterStone® may be thinned up to 10% with water for the last step.

## Tips:

Always make a sample to ensure the desired result.

Mix thoroughly before each use.

Under normal conditions, no topcoat is required. A topcoat may be used in areas such as kitchens and bathrooms where extra protection is required.

When repairing, sand the damaged area and wipe down. Reapply LusterStone® in thin, even coats.

Close the container after each use. Keep airtight. Keep the sides and edges of the container clean. Do not allow dried product to fall into the wet material. A sheet of plastic wrap pressed onto the surface of the material will keep it from drying out and protect it from foreign matter.

LusterStone® can be applied to irregular surfaces such as ironwork and assorted fixtures by brush or spray.

On large walls the application process can be started and stopped at any point in the process without experiencing lap lines.

LusterStone® works well as a fill coat on textured surfaces.

